

APPLICATION FOR UNITED STATES LETTERS PATENT

for

SYSTEMS AND METHODS FOR STATE-LESS AUTHENTICATION

by

STEPHEN F. BISBEE

JACK J. MOSKOWITZ

KEITH F. BECKER

ELLIS K. PETERSON

and

GORDON W. TWADDELL

BURNS, DOANE, SWECKER & MATHIS, L.L.P.
POST OFFICE BOX 1404
ALEXANDRIA, VIRGINIA 22313-1404
(703) 836-6620
Attorney's Docket Number 003670-074

SYSTEMS AND METHODS FOR STATE-LESS AUTHENTICATION

BACKGROUND

This invention relates to authentication of users of electronic information and transaction processing systems, and more specifically to systems and methods for authenticating users of program objects in distributed computing environments based on negotiated security contexts.

Many computer and communication systems restrict access to authorized users. As typically shown in Fig. 1, a user 110 accesses such a system 120 through a suitable interface such as a computer 130 executing a client application. The computer 130 and client application can communicate with the system 120 by either a direct connection or via the Internet using a convenient protocol such as http as illustrated by connection 140. In accessing the system 120, the client application recognizes that a user authentication process must be carried out as a threshold step, and thus the client application usually requests the user 110 to enter a logon ID and a password that uniquely identify the user 110 to the system 120. The logon ID and password are conventionally forwarded to a logon component 122 via an application server component 124 included in the system 120.

The logon component 122 compares the logon ID and password received from the user to an archive of logon IDs and passwords stored in a rules database 126. Upon finding a match with the forwarded logon ID, the logon component 122 retrieves the corresponding password from the rules database 126 and compares the retrieved password with the password forwarded by the user 110. If the passwords match, the logon component 122 sends an instruction or a message via the application server component 124 to the client application in computer 130 that indicates that the user 110 been properly identified and authenticated to proceed. This authentication step and/or subsequent instructions or messages may initiate a secure communication session using a convenient protocol such as https indicated by connection 150. Subsequent communication between the system 120 and computer 130 can then proceed in private.

Where encryption is employed, a client cryptographic token such as an electronic circuit card conforming to the standards of the PC Memory Card Interface Association (a PCMCIA card or PC Card) can be used in the computer 130. In general, a token is a portable transfer device that is used for transporting keys, or parts of keys. It will be understood that PC Cards are just one form of delivery mechanism; other kinds of tokens may also be used, such as those conforming to RSA Laboratories' software token Public-Key Cryptography Standard (PKCS) #12, floppy diskettes, and Smart Cards.

If the logon ID provided by the user 110 does not match an ID in the rules database 126 or if the password comparison fails, the logon component 122 typically sends a message or instruction through the application server component 124 to the client application to inform the user 110 that the submitted logon information was incorrect and to prompt the user to re-enter it.

5 This process of entering and attempting to verify the logon information may be permitted to occur a few times, but in the event of repeated failure, the logon component 122 may finally reject further logon attempts by the user 110, direct the client application to inform the user 110 that the logon process has failed, terminate the communication session, and lock out the user from any further logon attempts.

10 A password is one form of identification that may be presented to the logon component 122 that authenticates the user's access rights, which may range from simply viewing selected records in the system 120 to performing all transactions permitted by the system 120. This kind of secured transaction processing is typically "state-full" in that it maintains, in the transaction session, the process state and content of the user's logon access information. Different
15 transactions are typically implemented in modern distributed, nested, transaction processing systems by different program objects, e.g., applications or subroutines, that are substantially independent, even to the extent of executing on different processor hardware. For a user to migrate from one secured transaction to another, which is often necessary for even simple uses of today's systems, the user is generally required to logon (i.e., be authenticated) to each
20 transaction, often with ID's and passwords unique to each transaction. This is because state-full systems impose state routing restrictions on users, and only sessions with particular restrictions can service a given user without having to close one program object and open another, with the corresponding requisite logon.

Besides the burden on system resources imposed by each logon, which requires access to
25 and processing by a logon component and a rules database, state-full systems often compel each user to close one secured transaction (program object or application) before entering another, limiting the flexibility of the system from the user's perspective. In addition, if the path to the rules database is closed or if excessive traffic slows processing or access to any of the necessary components of the system, the user access to the desired application is compromised, even if the
30 user's access is fully authorized. This becomes a significant problem for systems having many potential users because economics often limits the system resources that can be made available.

Another problem is that conventional enrollment systems can be viewed as "open doorways" into an otherwise protected application in that a successful logon provides a user full

access to the application and a failed logon "slams the door" on access to the application. No middle ground is generally provided, whereby a properly identified user is provided partial access to an application or transaction.

Yet another problem with systems like that depicted in Fig. 1 is the vulnerability of such systems to a hacker's or a pirate's intercepting a user's logon information at any of several points and then gaining unauthorized access to a supposedly secure system, such as an online brokerage system. One countermeasure to such interception is the application of cryptography to the data being transmitted. Public-Key Cryptography (PKC), or asymmetric cryptography, is a form of data encryption that uses a pair of cryptographic keys, each pair having a public key that is used for encryption and a private (secret) key used for decryption. Exemplary PKC algorithms, which comply with contemporary government or commercial standards, are the Digital Signature Algorithm and the Rivest-Shamir-Adleman (RSA) algorithm. The alternative to PKC is a symmetric key cryptographic system that uses the same key for encryption and decryption. Exemplary symmetric systems are the Data Encryption Standard (DES) and its improvement, the Advanced Encryption Standard (AES), recently announced by the National Institute of Standards and Technology (NIST). Symmetric key cryptography is normally employed for encrypting large amounts of data since it is much faster than PKC, but PKC is still advantageously used for key distribution. Nevertheless, encrypting transmitted data may address privacy concerns in electronic commerce and communication, but encryption alone does not address the issues of integrity and authentication of the transmitted information.

In this application, "privacy" means the protection of a record from unauthorized access. "Integrity" means the ability to detect any alteration of the contents of a record or of the relative authority of a user to perform a transaction or access a record. "Authentication" means verification of the authority of a user to perform a transaction, use a system resource, or access an electronic record. It will be appreciated that "electronic record" and "record" mean information in any electronic form, regardless of type of medium or type of information. Thus, a record can be a tape cartridge, a voice transmission or recording, a video image, a multi-media object, a contract, metadata, a database of information, etc.

Integrity and authentication of information are typically handled by other cryptographic operations, in particular hashing the information to be protected and appending one or more digital signatures. In general, a one-way cryptographic function operates on the information and produces a "hash" or "message digest" in a way such that any change of the information produces a changed message digest. Since a different message digest is produced if even one bit

of the information object is changed, the hash operation yields a strong integrity check. Known hashing algorithms are the Secure Hash Algorithm (SHA-1) and the Message Digest 5 (MD-5) algorithm, and new algorithms appear from time to time. Information is typically digitally signed by hashing the information, encrypting the resulting hash using the signer's private key, and appending the encrypted hash to the information. Thus, digital signatures are generated in a manner like PKC, but the keys are reversed: the encryption key is private and the decryption key is public; the digital signer signs information with the private key and a user can read the digital signature with the signer's public key. Since a digital signature is a non-forgeable data element attached or allocated to information that ties the signer to the information, the digital signature yields an authentication check. It will be appreciated that a digital signature differs from a holographic, or handwritten, signature and from a digitized holographic signature, which is a handwritten signature that has been captured electronically.

The uses of digital signatures typically involve uses of authentication certificates, which are non-forgeable, digitally signed data elements that bind the signers' identity information to the signers' public-key information. Authentication certificates have been standardized by the International Telecommunications Union (ITU) under International Standard X.509, as documented in "The Directory-Authentication Framework" (1988) and as interpreted by the Internet Engineering Task Force Public Key Infrastructure X.509 recommendations. An authentication certificate is digitally signed and issued by a Certification Authority that is responsible for ensuring the unique identification of all users. Each authentication certificate typically includes the following critical information needed in the signing and verification processes: a certificate version number, a serial number, identification of the Certification Authority that issued the certificate, identifications of the issuer's hash and digital signature algorithms, a validity period, a unique identification of the user who owns the certificate, and the user's public cryptographic signature verification key. A signer's authentication certificate may be appended to information to be protected with the user's digital signature so that it is possible for others to verify the digital signature.

Single-logon methods have been implemented in which a logon component returns a "cookie" or token to a client application that allows the client application system-wide logon in a distributed computing environment. One example of this is the SITEMINDER software product made by Netegrity, Inc., Waltham, Massachusetts, and described at www.netegrity.com. Such single-logon methods avoid the need for repeated logons, but have severe limitations when used with state-less computing environment components.

U.S. Patents No. 5,757,920 for "Logon Certification" and No. 5,999,711 for "Method and System for Providing Certificates Holding Authentication and Authorization Information for Users/Machines", both to Misra et al., describe logon certificates that are provided to support disconnected operation in distributed computing systems. Each logon certificate is a secure package holding credentials information sufficient to establish the identity and rights and privileges for a user or a machine in a domain that is not the user's/machine's home domain.

U.S. Patent No. 5,241,594 to Kung for "One-Time Logon Means and Methods for Distributed Computing Systems" describes storing password files in all networked computers in a distributed system and, after a user logs on to a computer, forwarding authentication information to a second computer using a secure transport layer protocol if the user wishes to use services at the second computer. The second computer compares the user's authentication information it receives with the user's authentication information it stores, and if the informations match, the user is logged on to the second computer.

Other logon methods and systems are described in U.S. Patents No. 5,655,077 to Jones et al. for "Method and System for Authenticating Access to Heterogeneous Computing Services"; No. 5,689,638 to Sadovsky for "Method for Providing Access to Independent Network Resources by Establishing Connection Using an Application Programming Interface Function Call Without Prompting the User for Authentication Data"; No. 5,768,504 to Kells et al. for "Method and Apparatus for a System Wide Logon [sic] in a Distributed Computing Environment"; No. 5,774,650 to Chapman et al. for "Control of Access to a Networked System"; No. 5,884,312 to Dustan et al. for "System and Method for Securely Accessing Information from Disparate Data Sources through a Network"; and No. 6,178,511 to Cohen et al. for "Coordinating User Target Logons in a Single Sign-On (SSO) Environment".

sub A1 The problems with systems like that shown in Fig. 1 are keenly felt in many computer and communication systems, including as just one example those employed in electronic commerce. As paper documents that have traditionally recorded transactions, such as the purchase of an object, the withdrawal of bank funds, or the execution of a contract, are replaced by electronic records, serious issues of physical control of the electronic records and access to them are raised. Systems and methods for providing a verifiable chain of evidence and security for the transfer and retrieval of electronic records and other information objects in digital formats have been described in U.S. Patents No. 5,615,268; No. 5,748,738; and No. ____; all to Bisbee et al., and U.S. Patent Applications No. 09/452,928, filed on December 2, 1999, and No. 09/737,325, filed on December 14, 2000, both by Bisbee et al. These patents and

applications are expressly incorporated here by reference, and describe among other things flexible business rules that enable users to have roles that are required or enabled only at particular points in a transaction or process. For example, a user may have a role of title agent only after a transaction has closed.

5 Such work flows and processes can be more complex than those typically associated with single-logon techniques. Moreover, many electronic records available to online inquiry are neither encrypted, nor hashed, nor digitally signed since to do so increases the processing time and resources needed for authorized users to access such information.

10 SUMMARY

This invention solves the above-described and other problems suffered by computer and communication systems having restricted access, providing methods and systems for providing secure access to information in an on-line, networked environment in which traditional methods of verification, integrity, and authentication are generally inapplicable or ineffective. Important features of the invention involve an encrypted data element called a security context, which is securely built and accessible only by a trusted computing environment, thereby eliminating the risk of interception, modification, or unauthorized use.

15 In one aspect of the invention, a security context is built from a user's logon information and from system authorization information that define the user's access rights to protected on-line applications and electronic information. The security context is hashed and encrypted to protect the included logon and access information from theft and misuse. Following a successful logon that establishes a respective security context, the user may seek access to applications, transactions, and records without having to re-logon and without having to re-access a logon rules database. This does not preclude the user from requesting a new security context if necessitated by a change in either the user's role in a transaction or the type of transaction. A user's level of access can be controlled by a plurality of identifiers, such as the user's logon ID, the user's organization ID and sub-organization ID's, and the user's particular role or credentials within the organization. System resources protected in accordance with this invention are not limited to electronic records and computer-directed applications and transactions but also extend to secured equipment, such as facsimile machines and certified printers.

25 In another aspect of the invention, a method of enabling access to a resource of a processing system includes the steps of establishing a secure communication session between a

user desiring access and a logon component of the processing system; verifying that logon information, provided by the user to the logon component during the secure communication session, matches stored information identifying the user to the processing system; generating a security context from the logon information and authorization information that is necessary for access to the resource; providing the security context to the user; and sending, by the user to the processing system, the security context and a request for access to the resource. The resource may be at least one of a processor, a program object, and a record of the processing system, and the logon component may provide a symmetric encryption key to the user in establishing the secure communication session. The user may digitally sign the request for access, the user's digital signature may be included with the request for access in a wrapper that is sent with the security context to the processing system, the user's digital signature may be checked by the processing system, and access to the resource may be granted only if the user's digital signature is authenticated.

The logon information may include a password and at least one of a user identifier, an organization identifier, a sub-organization identifier, a user location, a user role, and a user position. The logon information may be verified by checking for agreement between the stored information identifying the user to the processing system and the password and at least one of a user identifier, an organization identifier, a sub-organization identifier, a user location, a user role, and a user position provided by the user to the logon component.

The security context may include a plaintext header and an encrypted body, and the plaintext header may include a security context ID, a key handle, and an algorithm identifier and key size. The encrypted body may include at least one of a user identifier, an organization identifier, access information, an expiration time, public key information, symmetric key information, and a hash, and access to the resource may be denied if the expiration time differs from a selected time. The access information may specify at least one resource accessible by the user; the expiration time specifies a time after which the security context is invalid; and the hash is computed over the plaintext header and the encrypted body before encryption, and may be digitally signed by the logon component.

The method may further include the step of determining, by a stateless component of the processing system, based on the security context sent with the request for access by the user, whether access to the requested resource should be granted to the user. The request for access may be at least partially encrypted with a symmetric encryption key extracted from the security context. A hash value may be computed over the request for access and be included with the

security context and the request for access sent by the user to the processing system, with the integrity of the request for access being checked based on the hash value, and access being granted only if the integrity of the hash value is verified. A request counter may be included in the request for access, and if access is granted, a response is sent to the user that includes the a request counter, enabling the user to match the response to the request for access. A response can also be an acknowledgement of an action performed (e.g., creation of a "certified" printout of a record).

In another aspect of the invention, a processing system having resources, such as processors, program objects, and records, that are selectively accessible to users includes a communication device through which a user desiring access to a resource communicates sends and receives information in a secure communication session with the processing system; an information database that stores information identifying users to the processing system and authorization information that identifies resources accessible to users and that is necessary for access to resources; and a logon component that communicates with the communication device and with the information database, wherein the logon component receives logon information provided by the user during the secure communication session, verifies the received logon information by matching against information identifying the user to the processing system that is retrieved from the information database, and generates a security context from the received logon information and authorization information. The logon component provides the security context to the user's communication device, and the user sends, to the processing system, the security context and a request for access to a resource. The processing system may further include a cryptographic accelerator, and the logon component may receive a symmetric encryption key from the cryptographic accelerator and provides the symmetric encryption key to the user's communication device.

Other aspects of the invention are described below.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other objects and advantages of this invention will become more apparent from the following description, read in conjunction with the drawings, of which:

Fig. 1 is a block diagram of user authentication in existing processing systems;

Fig. 2 is a block diagram of user enrollment in a system in accordance with this invention;

Fig. 3 is a block diagram of user authentication in a system in accordance with this

invention;

Fig. 4a is a diagram of a security context in accordance with this invention;

Fig. 4b is a diagram of a plaintext header of a security context;

Fig. 4c is a diagram of a body of a security context;

Fig. 5 is a block diagram of a user interacting with a secured client application in a system in accordance with this invention;

Fig. 6a is a diagram of a security context associated with a user request or submission;

Fig. 6b is a diagram of a security context associated with a user request in which a time parameter and a request counter are additional authentication factors;

Fig. 7 is a diagram of the system response to a user request or submission; and

Fig. 8 illustrates methods in accordance with the invention.

DETAILED DESCRIPTION

It will be appreciated that Applicants' invention can be implemented utilizing commercially available computer systems and technology, and since the details of such are well known to those of skill in the art, they will not be described in this application.

In using secure transaction processing systems, even in a system such as that depicted in Fig. 1, a system administrator usually must enroll a user with the system by entering identification, authorization, and attribute information that uniquely describe the user to the system. This is depicted in Fig. 2, which shows a user's enrollment information being provided by a known authority 210 to a system administrator 220, which enters the enrollment information into a trusted computing environment (TCE) 230. Entered information may include such items as the user's name, user identification (ID), organization name, organization ID, and location.

The enrollment information is typically provided to an interface device such as an application server component 232 that communicates with a logon component 234 of the TCE 230. The logon component 234 or an equivalent device generates a password for the user and securely stores the password in a protected rules database 236. Since password generation and protection is often processing intensive, the TCE 230 may include a suitable cryptographic accelerator 238 or other special-purpose processor that implements the cryptographic algorithms used for generating and checking passwords and for other operations. The password is securely delivered to the user via the application server 232 and an approved courier 240. The approved courier 240 may be a traditional overnight service, such as Federal Express, that delivers the

password in physical form, or an e-mail server or a facsimile machine that delivers the password electronically. The user receives the password (block 250) and must present the password to the TCE system 230 before access is granted. The TCE is so named because it includes the elements necessary for authenticated access to the transactions offered through the application server 232.

Many of the components for enrolling a user as depicted in Fig. 2 have additional important functions. In particular, enrollment information solicited by the system administrator and provided by a known authority to uniquely identify the user to the TCE 230 is extensive. For example, the enrollment information preferably includes organization name, organization ID, role, and optionally, location and multiple sub-organization names and IDs. The known authority may typically be associated with a sponsoring organization or other entity that endorses the user's access to secured system resources and is known to the system 230. While the known authority or sponsoring organization generally provides the user's enrollment information to the system 230, the user may also provide the information.

The logon component 234 examines all received enrollment information for compliance with rules and requirements maintained in the rules database 236, which must be protected storage to ensure the integrity of the identification and authorization information it maintains. Any received enrollment information that is not in compliance preferably causes a message to be displayed or other indication to be given to the information submitter to prompt submission of correct information. In general, the rules database 236 may be initialized with user authorization and attribute information in the form of data, flags, algorithms, business rules, etc. With this information, as will be discussed more thoroughly below, the system can provide varying levels of authorized access to system resources, depending on the particular organization or sub-organization the user represents and the role the user plays in accessing particular transactions and/or records.

As with conventional systems, the enrollment information obtained by the system administrator is passed to the logon component 234, which instead of merely storing a password in the rules database 236, first processes the password through a suitable protective method or device such as a hashing algorithm and stores the hashed password in the rules database such that it is associated, or linked, to the particular user by the user's logon ID and optionally by the user's organization ID. The logon component 234 then forwards the unhashed (plaintext) password to the user through any of the secure communication channels discussed above. After a user has been enrolled by the system 230 and has received a password, the user can access

system applications, components, transactions, and records, but only after the user is authenticated as having authority to access the secured resources.

Fig. 3 is a block diagram depicting user authentication in accordance with an aspect of this invention. After a User 310 invokes a protected Client Application 320, whether via a direct connection to a TCE 330 or via an Internet browser, control passes automatically from the user-invoked application via an Application Server 332 to a Logon Component 334 to attempt authentication of the User 310 through the exchange of secured logon information. As indicated in Fig. 3, the Client Application 320 may execute in a suitable computer or terminal having a Cryptographic Token as described above in connection with Fig. 1. One function of the Logon Component 334 is generating a private/public encryption key pair at pre-selected time intervals for use in creating secret symmetric sessions between the User 310 and the Logon Component 334. Rather than being generated by the Logon Component 334 alone, the key pairs may advantageously be generated in cooperation with an otherwise conventional Cryptographic Accelerator 338, in which case "handles" associated with the private key and public key of a key pair are provided to the Logon Component 334 for convenience of processing.

In these secret symmetric sessions, encrypted logon information is exchanged and passwords are validated as more thoroughly discussed below. Encryption helps to secure the integrity of the information exchanged between the User 310 and the Logon Component 334 during the logon process and to minimize the possibility that any of the logon information can be intercepted and used for unauthorized access to system resources. By generating and utilizing the encryption keys internally, the system 330 precludes external, unauthorized access to the keys.

The encryption key pair that has been most recently generated can be called the "current" key pair and is preferably allocated to all logon processing until the next key pair is generated. Key pairs advantageously are usable for respective limited periods of time, so that an earlier encryption key pair persists until it expires.

As an alternative to private/public encryption key pairs, the Logon Component 334 can use a known key exchange algorithm/protocol to generate a secret symmetric session encryption key. Exemplary algorithms for creating secret symmetric keys are the Diffie-Hellman algorithm and the Key Exchange algorithm of the NIST. Even so, it is currently preferred to use application server-side authentication employing an X.509 authentication certificate that enables establishment of a secure socket layer (SSL) session. As yet another alternative, user and server authentication certificates can be used to establish a two-way authenticated SSL session. The

advantage of either SSL approach is its facilitation of the use of the Cryptographic Token and the Cryptographic Accelerator 338 that relieves both the user and the Application Server 332 processors from the burden of carrying out the cryptographic operations.

After a secret symmetric key is determined by the Logon Component 334, it is routed to the User 310 to establish a secure session, in which encrypted information can be exchanged by the User 310 and the Logon Component 334. The Logon Component 334 then requests logon information from the User 310. In response, the User 310 transmits its identity information and the local time ("Client Time") to the Logon Component 334.

The user's identity information preferably includes its logon ID, organization ID, password or shared secret (e.g., a personal identification number (PIN), a passphrase, biometric information (fingerprint, retina scan, voiceprint, etc.)), etc. The user's logon ID advantageously becomes the relative basis for accessing user-related authorization information in the Rules Database 336. The organization ID can include a hierarchy of IDs, each representing a sub-organization within the organization, such as a subsidiary or a department, to which the user may be associated. Additionally, the identity information can include user functional data, such as the user's role, position, or credentials in the organization. The password provided by the User 310 is typically hashed at the user's side of the exchange prior to transmission to the Logon Component 334 to provide an additional level of protection against unauthorized capture of the password during transmission. Further protection against unauthorized access to the user's password may be obtained by encrypting the password, e.g., according to RSA Laboratory's PKC Standards (PKCS) #5 - Password-Based Cryptography Standard, using the secret symmetric key received from the Logon Component 334. The Client Time may also be provided during logon as an anti-spoof feature which will be described later in this description.

The Logon Component 334 decrypts the user-entered logon information if necessary, using the Application Server-side symmetric key and the Cryptographic Accelerator 338, and compares the logon information to the authorization information in the Rules Database 336, as linked by the entered user logon ID. The hash of the password entered by the User 310 is compared to the hashed password stored in the secured storage of the Rules Database 336, also as linked by, or related to, the entered user logon ID to determine that the two hashes match. If any of the identification and authentication information submitted by the User 310 is in error or fails to match the data or rules in the Rules Database 336, the User 310 is challenged by the Logon Component 334 to check and resubmit the User's information. After a predetermined number of failures, the logon session, and thus the User's access attempt, will be terminated.

Such a limit helps prevent a brute force password attack. The User 310 may attempt to logon again, but several more sequential repeats of the logon failure, as determined by system security attributes in the Rules Database 336, will lock out the User 310 and will alert a system security officer. Alternatively, the Logon Component 334 may disable the User's logon ID in the Rules Database 336 until a system security officer can review the logon failures.

After the User's identification and password information have been presented and verified, the Logon Component 334 retrieves the User's authorization information from the Rules Database 336, as linked by the user's logon ID and conditioned on the user's organization ID(s) and role(s). Authorization information may be built at this point based on the user's organization ID(s) and role(s) as determined by any corresponding business rules in the Rules Database. The Logon Component 334 then creates a Security Context that conveys the user's identity and other relevant authorization information necessary to gain access to Application Server-based system resources, including online transactions and electronic records. This identity and authentication information is sufficient to qualify the User for the full range of activities needed to carry out those actions and accesses previously authorized for the User.

Referring now to Figs. 4a, 4b, and 4c, and initially to Fig. 4a, a Security Context is built that comprises a Plaintext Header and a Security Context Body. The Plaintext Header, shown in more detail in Fig. 4b, comprises a Security Context ID, a Key Handle that permits retrieval of the selected secret symmetric key, and an Algorithm Identifier, including the Key Size of the selected symmetric key. The Security Context Body, shown in more detail in Fig. 4c, comprises at least some of user and organization identities; role and access information; Bypass Flag(s); a Time-Offset information element (the difference between the User's Current Time and the TCE's current time); an Expiration Time information element (the time later than which the Security Context is invalid); the User's Public Key Algorithm identifier, Key Size, and Public Key; the Symmetric-Session/Request Key Algorithm identifier, Key Size, and generated Symmetric Key; a known value or random number, and a hash or other suitable check value computed over the Plaintext Header and the Security Context Body content. Including the hash value in the Security Context Body ensures that the Security Context content cannot be modified without detection.

To eliminate any possibility of forgery or unauthorized alteration, the Security Context hash may be digitally signed by the Logon Component 334. The authentication certificate of the Logon Component may be made available to all system components.

The Security Context Body is then encrypted using the Logon Component-specified

symmetric or the generated private key referenced by the respective Key Handle. The Security Context and the symmetric session encryption key contained therein are then forwarded to the User and retained for the period for which the Security Context is valid. In some instances, the Time-Offset and Expiration Time values may also be returned to the User, which allows the User to renew the Security Context prior to its expiration.

At this point, Security Context building, encryption, and placement are completed and communication between the User and the Logon Component are terminated. Transaction-level communication between the User, Client Application, and TCE are re-established.

Referring to Fig. 5, there is illustrated an embodiment of this invention in which a User 510 seeks access to protected applications (program objects) and records available from the TCE 530 via a Client Application 520 and Cryptographic Token. As can be seen from Fig. 5, the TCE 530 includes Stateless System Components 535 that are Application Server-side program objects that are instantiated to satisfy user requests for processing or information. The term "stateless" indicates that no request history is retained and the authentication methods of the system are independent of the particular state, or application/transaction/routine, being invoked.

The Stateless Components 535 may be considered as existing at an "industry level" or at a "core level". Core-level components are reusable program objects that are industry-independent and thus will be understood as those components that are typically at the heart of any processing system. Thus, core-level components are used by all users of the TCE. The strongest security enforcement is found at the core level where access restrictions can be enforced broadly. Industry-level components are also reusable program objects but are industry-dependent. Thus, industry-level components are used by only a subset of all users of the TCE, i.e., the subset of users that can be categorized as the respective "industry". It will be appreciated that this description of different levels is merely for organizational convenience and that one or more levels may be employed.

It will be understood that the operation of the TCE 530 is effectively transparent to the User 510, who simply logs onto the system and operates as the User would in an otherwise conventional distributed processing system. An important difference is that a permanent session does not have to be established between each User 510 and Application Server-side components in the TCE 530. Application Server-side components can therefore be stateless since all the information needed to authenticate a User's request is communicated in the Security Context that is included in the User's request. After a Stateless System Component 535 finishes a task, it is free to service another User's request.

Referring again to Fig. 4c and also to Fig. 3, the User ID represents the User's logon ID, and the Organization ID represents the organization to which the User belongs. As discussed above, the Organization ID field can be expanded to include Sub-Organization ID's which represent subsidiary or departmental divisions under a primary organization. One advantage of this is that a single User, who may be affiliated with multiple organizations, subsidiaries, and/or departments, can have different levels of access authorized as a function of the particular organization or group that the User is representing at the time of logon. Similarly, the Roles, Credentials, and Other Authorization Information field comprises additional levels by which access can be controlled, depending on who the User is and what role or responsibility the User is fulfilling at the time of logon. These elements and rules permit customized access to protected system resources, depending, for example, on whether a User is acting as an owner, manager, agent, etc. These authorizations or access permissions are preferably established with sufficient granularity to achieve system and application security policy objectives.

A Bypass Flag(s) field indicates which, if any, security features are disabled. This reduces computation overhead when the Security Context is used among Stateless System Components 535 in an otherwise protected and trusted environment, as discussed more thoroughly below. Although illustrated as a single field, a Bypass Flag may be associated with each security feature to indicate whether or not the feature is used.

A Time-Offset field is used by the Logon Component 334 and Stateless System Components 535 to adjust for discrepancies between TCE system (current) time and Client Time, which is the time at the User's computer or browser (see Fig. 6b). This facilitates operation of the Security Context and TCE in environments where time synchronization among User and system components is not available. This feature can compensate when a component's internal clock is otherwise stable and within normal tolerances.

An Expiration Time field identifies the time of expiration of the Security Context, placing an upper limit on the life of the Security Context. This is enforced by the Stateless System Components 535 and can be used by Users to renew their Security Contexts. An Expiration Time is also associated with every Security Context encryption key. Exceeding the Expiration-Time value forces the Logon Component 334 to create a new Security Context encryption key. In this way, the number of Security Contexts that are protected by a given key and uses thereof can be limited. The Security Context encryption keys are deleted on the Application Server-side after the Expiration-Time value is exceeded, and thus subsequent attempts to access transactions or records using Security Contexts with outdated encryption keys

fail. Either symmetric or asymmetric encryption may be employed.

The Logon Component 334 may also establish a maximum count for the number of times a particular Security Context encryption key is used. When the count in a Request Counter field (see Fig. 6b) exceeds this pre-established threshold, the Logon Component 334
5 may be asked to create a new Security Context.

The User Public Key Algorithm field may contain an algorithm ID, key, and/or Authentication Certificate. The public key pair may be generated by the Logon Component 334 or the Client Application, or created in conjunction with the issuance of a user's X.509 authentication certificate and public-key pair delivered in a Cryptographic Token. The private
10 key is held at the User's location, possibly in a hardware Token. The public key is passed to the Logon Component 334 during symmetric session key negotiations or is passed in the user's X.509 certificate. To reduce processing overhead, the public key information may be extracted from the X.509 certificate and placed directly in the Security Context.

Referring again to Fig. 5, with a Security Context having been established for each User
15 510 logging onto the system 530 with a particular logon ID, organization ID, password, and optionally, role identifier, the authority of each User 510 as verified through the Stateless System Components 535 can be determined without having to preserve any user-specific state information and without having to access a rules or authorization file. In other words, the Stateless System Components 535 need not maintain knowledge regarding any particular active
20 User 510 or invoked Stateless System Component 535. All such knowledge is passed in the encrypted Security Contexts. In this way, a plurality of stateless system components can be instantiated simultaneously and/or on an as-needed basis and transaction and information routing restrictions can be removed, since each Security Context/User Request is treated independently. Therefore, a plurality of secure digital components may be simultaneously accessed merely by
25 forwarding an authenticated user's Security Context to the validation portion of each Stateless System Component.

All Stateless System Components 535 that may be asked to perform some action or to access desired information in response to a User request must be given access to the User's Security Context to determine whether the requested action or access is authorized. Since the
30 Security Context is encrypted, the Stateless System Components 535 are provided with the right to use the cryptographic key identified in the Plaintext Header to read the contents of a particular Security Context, including the Authorization Information, in conjunction with the set of cryptographic services performed by the Cryptographic Accelerator 538. In addition to

implementing controls to limit User access to protected Components, this invention may also be applied to automatically authenticate action and access requests between Stateless System Components 535 themselves.

Following successful creation of a Security Context for a given user logon session, the Security Context can be effectively applied in several ways to control securely and efficiently user access to protected program objects and records. As illustrated by Figs. 5 and 6a, a User appends its User Request or Submission to the encrypted Security Context it has received in order to provide a secure access instruction/authorization to the Application Server 532 and Stateless System Components 535 to fulfill the User's Request. Referring to Fig. 6a, a User Request, which may be directed to an action request, transaction access request, or record access request, among other things, is appended to the encrypted Security Context and forwarded through the Application Server 532 to the appropriate Stateless System Component 535. Alternatively, the User Request may be a data submission to modify or replace an existing protected record.

It will be appreciated that the User Request or Submission depicted in Figs. 5, 6a, and 6b, and for that matter substantially any of the communications described or necessitated by this description, can be enclosed in a "wrapper", which is a kind of envelope that is used to securely hold and associate digitized handwritten and cryptographic digital signatures with part or all of one or more electronic information objects or data contained in the wrapper. Wrappers may take the form of any open standard enveloping or information object (document) formatting schemas, and generally a wrapper is a data structure containing tags that permit locating and extracting information fields contained in the wrapper. Two examples are RSA Laboratories' PKCS #7 and the World Wide Web Consortium (W3C) Extensible Markup Language (XML) Signature Syntax and Processing Draft Recommendation, although any record format supporting inclusion of digital signatures with content may be used, including, but not limited to, S/MIME, XFDL, HTML, and XHTML, which provide support for signature syntax, processing and positioning (tags). The PKCS #7 standard supports zero, one, and multiple parallel and serial digital signatures (cosign and countersign) and authenticated and unauthenticated attributes that are associated with the signatures. Information elements that may be contained in wrappers include algorithm identifiers, key size for each algorithm, content, and signatures, and wrappers can be applied recursively, which simply means that wrappers can be contained within wrappers.

Upon receipt of a Security Context/User Request, a Stateless System Component 535 directs the decryption of the Security Context. The Stateless System Component 535 first uses

the Plaintext Header Key Handle and Algorithm Identifier information to identify the corresponding cached decryption key to the Cryptographic Accelerator 538. A number of active symmetric and asymmetric encryption and decryption keys are held in protected storage by the Cryptographic Accelerator 538, and each is referenced by a unique handle contained in a Security Context header as described above. The Stateless System Component 535 then enables the Cryptographic Accelerator 538 to decrypt the Security Context Body and User Request, which make the User's identification and access authorization information and the request contents available to the Component.

The Stateless System Component 535 verifies the integrity of the received Security Context and User Request by verifying the respective hashes and/or the digital signature, if used. The Stateless System Component 535 compares the roles, credentials, and authorization information from the decrypted Security Context Body with the User Request. If there is a mismatch between the authorization information and the Request, the access attempt fails and the User 510 is so notified, and control is passed back to the User 510 either to submit another Request or to terminate the session. Similarly, if the time of submission is outside the Expiration-Time window for the Security Context, then the access attempt fails. If insufficient information exists in the Security Context authorization information field, the Stateless System Component 535 may access the Rules Database 536 for additional information. If insufficient information still exists after accessing the Rules Database 536, the access request fails, and the User 510 is so notified. If the access verification process has been successful, then the Stateless System Components 535 are permitted to proceed with fulfilling the user request, with a response ultimately being directed back to the User 510.

As illustrated by Fig. 6b, Client Time and Request Counter fields may be included in the Security Context/User Request data stream. The Client Time represents the time at the User's computer, terminal, or other system access device. The User may be given the option of comparing Client Time, as adjusted by a Time-Offset value, to the Expiration-Time limit. If the adjusted Client Time exceeds the Expiration Time, the User then knows that any authorization and access requests will fail, and the User can efficiently logoff and log back on or otherwise initiate a new session, thereby creating a new Security Context with a new Expiration Time. If the User (Client Application) is not enabled to perform this check, rejection of any and all requests, termination of the session, or a direct alert will force the User to create a new Security Context.

The Request Counter field is typically initialized at zero at the creation of the Security

Context and is incremented each time a User Request with this particular Security Context is directed to the Stateless System Components 535. In this way, use of the Security Context can be limited, with the User being denied access should the Request Counter exceed a predetermined maximum. It will be appreciated that decrementing Request Counters can also be used. Additionally, the Request Counter may be used to match Requests with System Component responses when responses are returned asynchronously (out of chronological order). Thus, a request counter is included in the request for access, and If if access is granted, a response is sent to the user that includes the arequest counter, which the user uses to match the response, which may be an acknowledgement of an action performed (e.g., creation of a "certified" printout of a record), to the request. Finally, the Request Counter can prevent "replay" attacks, in which a hacker intercepts a User Request or Component Response and falsely presents the Request for access to a protected transaction or record or replays the Response to create network and system congestion. The system 530 and client application 520 both recognize when the Request Counter in the Security Context/User Request data stream is out of synchronization with previous Requests and reject the false Request. Alternatively, Client Time (Fig. 6b) can also be used to prevent replay attacks.

In another embodiment, the User Request portion of the secured Security Context/User Request stream depicted in Figs. 6a, 6b may be encrypted prior to being passed to the Stateless System Components 535, utilizing the symmetric key or the public key held by the User and disclosed in the Security Context. Encryption of all or part of the User Request additionally protects against an outsider threat or disclosure of sensitive information. Since the encryption key is internally selected within the Logon Component 334 and passed internally to the User within the Security Context or within a secure session with a login component, and because each encryption key has a limited life by application of the Expiration-Time feature, outsider access to a User Request for unauthorized use is substantially impossible. Upon receipt of the User Request, the cached decryption key is identified by the Stateless System Component 535 and used to decrypt the Request.

In another embodiment, all or part of a User Request may be hashed prior to being forwarded to the Stateless System Component 535, with the hash value being appended to the User Request. The Stateless System Component 535 would then hash the received User Request and compare its result with the hash value appended to the User Request. If the two hash values match, the system can be reasonably assured that the User Request has not been modified. If the two hash values do not match, the User-side application can be instructed to

re-send the Security Context/User Request/Hash data stream, or a message can be sent to the User advising that receipt of a corrupt Request resulted in failure prior to the request authorization process.

In yet another embodiment, a digital signature can be applied to all or part of the Security Context/User Request data, with the digital signature being verified upon receipt by the Stateless System Components 535. Upon verification or non-verification, the Stateless System Components 535 proceed as described above in connection with Request validation. Both the hashing and digital signature features help prevent middleman and substitution attacks on the access authorization process.

In yet another embodiment of the invention, encryption and hashing of the User Request are combined to provide a secure, non-forgable session for the authorized access of transactions and records.

Fig. 7 depicts a response to a User 510 by protected Stateless System Components 535. The response may be transmitted to the User in plaintext, relying on the integrity of the session encryption, or the response may be encrypted using the secret encryption key embedded within the Security Context and held by the User. As discussed above, the User advantageously utilizes the Request Counter field to match the response received from the system 530 with its User Request. This is particularly important when responses are returned asynchronously (out of order), such as when the Components 535 process multiple requests and when the User submits multiple access requests across a plurality of Application Servers 532.

It should be understood that a User does not have access either to the Security Context encryption key or to the contents of the Security Context. Only the Logon Component and Stateless System Components have such access. Use of a digital signature by the Logon Component prevents modification by any component, enabling the Security Context's content to be trusted. The User Request encryption key, Time Offset, and other relevant information needed by the User are passed to the User/Client Application during the secure Security Context setup session. It will be appreciated that both trusted and untrusted Stateless System Components can be used by layering the methods described here, increasing bit overhead as needed to achieve an appropriate level of protection.

Application of the methods described above is illustrated by Fig. 8, although it will be understood that not all of the features described above are included.

In block 802, a system administrator is instructed by an authorized source to enroll a user, whose identification and authorization information is entered into a system enrollment

database. The user is assigned a user ID and preferably an organization ID that uniquely identify the user to the system, although it will be understood that other means of uniquely identifying users may be employed.

Block 804 indicates that three password methods may be supported: initialize (requiring the system administrator's password); check (requiring the logon component's password); and change (requiring a user's current password). During enrollment, a default password may be created and assigned to the user. The hash of the default password is associated with the user's unique identity and saved in protected storage. The plaintext password is made available to the system administrator, who arranges for its delivery to the user, preferably using an out-of-band means, such as an approved courier. The logon component facilitates the user's changing its default password to one that is more memorable. A new password can be issued if the user forgets its password or believes its password may have been compromised or from time to time.

In block 806, a private key is used by the system's logon component to protect security contexts. A new PKC pair is generated at suitable intervals, which may vary by application or industry. The most recently generated key pair can be called the current key pair, and key pairs may conveniently be generated by any suitable hardware cryptographic accelerator. The handles of the private key and public key of the current key pair are made available to the logon component. The private key is accessible only to the logon component. Prior (non-current) key pairs persist until their respective expiration times are reached. This overlap is chosen to be sufficiently long as to minimize the need for Users to have to request new Security Contexts. The logon component uses only the current key pair.

In block 808, the public key handle is shared with trusted stateless system components that, as trusted components, must be implemented in a protected operating environment. Access to a trusted system component is granted by the logon component's sharing the current public key handle and the address of the cryptographic accelerator with the component. Access by any other component is blocked, for example by a software or hardware firewall. Any such components require a Security Context to access system resources.

In block 810, the first occurrence of a user's needing access to system resources (components) requires the user, through its client application, to initiate a communications session with the logon component. An SSL session is preferably invoked.

In block 812, if an SSL encrypted session is not used, the user's client application engages in an exchange with the logon component that results in a symmetric-session encryption key existing at both the client application and the logon component. This symmetric-session

encryption key is the basis of subsequent secure communications between the user and the system and authentication with all trusted stateless system components. The symmetric-session encryption key may be used to encrypt user service requests.

In block 814, the user presents its credentials to the logon component, which asks the user to enter its unique identifying information and password. At this point, the user may be given an opportunity to change its password, either its default password generated at enrollment or its current password. System security policy typically dictates how often a user must change its password.

In the following description, the logon information is encrypted using a session-symmetric key, although as noted above an SSL session could be used. The user's client application forwards the user-entered information to the logon component using a predefined self parsing data structure such as the following, in which {} indicate an encrypted value, subscript identifies a key, and [] indicate plaintext:

User ID,
Organization ID,
{Password,
Client Time}_{symmetric-session}

To change a user's password, the client application forwards the user-entered information using a data structure such as the following:

User ID,
Organization ID,
{Password,
New Password, New Password Confirmation,
Client Time}_{symmetric-session}

In block 816, the logon component decrypts the Password(s) and Client Time using the symmetric-session key and computes a Delta Time value, which is the difference between the Client Time and the system time of the core server. The user's Password is then hashed according to an algorithm such as SHA-1 and compared to a hash value stored in the system database. If the hashes match, the user's Password is validated, and if a change of Password is requested, the logon component initiates the Password change procedure. If Password validation fails, the user may be given one or more chances to submit a correct Password, as specified by system security policy, before being locked out of the system.

In block 818, after successful user/client logon, the logon component builds and returns

to the user/client a Security Context (SC) that preferably includes the following elements:

SC = [SC ID, Plain Text SC Header

AlgorithmID_{public-current},

KeySize_{public-current},

Handle_{public-current}]+

{ User ID, Encrypted SC body

Org ID,

Authorizations,

Bypass Flag(s)

Expiration Time,

Delta Time,

AlgorithmID_{symmetric-session},

KeySize_{symmetric-session},

Key_{symmetric-session},

Hash} Private-current

In block 820, the user/client application may submit requests to trusted stateless system components using the SC returned to the user/client by the logon component. The client does so by appending a request to the SC. Two examples of SC-request combinations follow:

[SC Header, {SC body} Private-current] [{Client time} symmetric-session, Request]

[SC Header, {SC body} Private-current] [{Client time, Request, Hash} symmetric-session]

In block 822, the SC and request are verified by any trusted stateless system component by using the stored key referenced by Handle_{Public-current} to decrypt the SC body, then extracting and using the symmetric-session key to decrypt the encrypted portion of the Request, validating the Request by at least checking that system time = Client Time ± Delta Time, and further verifying the request by validating a hash and/or client digital signature if used.

In block 824, if the SC and Request are successfully validated, then the stateless system component uses the content of the SC and Request to perform the requested actions. In this way, the stateless system component may act as a trusted proxy for the user/client. The result of the request, if fulfilled, is returned to the user/client application. If desired, the result may be encrypted using the symmetric-session key.

It will be understood that these methods and systems are effectively transparent to a user, who simply logs on to the system and operates as the user would in a conventional distributed system. An important difference is that a permanent session does not have to be established

between the user/client application and server-side components, which can be stateless since all the information needed to authenticate a user's request is communicated in a non-forgable security context. After a stateless system component finishes its task, it is free to service another user request. Additional request capacity may be obtained by simply adding application servers
5 and/or instantiating stateless system components (program objects). These additions will also be totally transparent to client applications.

Although preferred embodiments of the present invention have been shown and described, it will be appreciated by those skilled in the art that changes may be made in these embodiments without departing from the principle and spirit of the invention, the scope of which
10 is defined in the appended claims and their equivalents.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2